

# Ethyl Alcohol Hand Sanitizer

Kem Krest

Version No: 2.6

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 04/03/2020

Print Date: 04/03/2020

S.GHS.USA.EN

## SECTION 1 IDENTIFICATION

### Product Identifier

Product name	Ethyl Alcohol Hand Sanitizer
Synonyms	Hand Sanitizer; Hand Rub
Proper shipping name	Ethanol or Ethyl alcohol or Ethanol solutions or Ethyl alcohol solutions
Other means of identification	130045, 130046, 130095

### Recommended use of the chemical and restrictions on use

Relevant identified uses	Hand Rub/Hand Sanitizer to help reduce bacteria that potentially cause disease.
--------------------------	---

### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Kem Krest
Address	12785 Emerson Dr., Brighton, Michigan 48116 United States
Telephone	248-486-3800
Fax	248-486-3810
Website	Not Available
Email	sdsrequests@kemkrest.com

### Emergency phone number

Association / Organisation	CHEMTREC
Emergency telephone numbers	800-424-9300
Other emergency telephone numbers	Not Available

## SECTION 2 HAZARD(S) IDENTIFICATION

### Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Eye Irritation Category 2A, Flammable Liquid Category 2
----------------	---

### Label elements

Hazard pictogram(s)	
---------------------	--

SIGNAL WORD	DANGER
-------------	--------

### Hazard statement(s)

H319	Causes serious eye irritation.
H225	Highly flammable liquid and vapour.

### Hazard(s) not otherwise classified

Not Applicable

### Precautionary statement(s) Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.

Continued...

## Ethyl Alcohol Hand Sanitizer

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

## Precautionary statement(s) Response

P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

## Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
-----------	--

## Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

## Substances

See section below for composition of Mixtures

## Mixtures

CAS No	%[weight]	Name
7732-18-5	22.56-22.85	<u>water</u>
75-65-0	0.06-0.12	<u>tertiary butanol</u>
3734-33-6	<0.01	<u>denatonium benzoate</u>
64-17-5	71.33-72.68	<u>ethanol</u>
7722-84-1	0.05-0.34	<u>hydrogen peroxide</u>
56-81-5	2.09	<u>glycerol</u>

## SECTION 4 FIRST-AID MEASURES

## Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

## Most important symptoms and effects, both acute and delayed

See Section 11

## Indication of any immediate medical attention and special treatment needed

## Ethyl Alcohol Hand Sanitizer

For acute or short term repeated exposures to ethanol:

- ▶ Acute ingestion in non-tolerant patients usually responds to supportive care with special attention to prevention of aspiration, replacement of fluid and correction of nutritional deficiencies (magnesium, thiamine pyridoxine, Vitamins C and K).
  - ▶ Give 50% dextrose (50-100 ml) IV to obtunded patients following blood draw for glucose determination.
  - ▶ Comatose patients should be treated with initial attention to airway, breathing, circulation and drugs of immediate importance (glucose, thiamine).
  - ▶ Decontamination is probably unnecessary more than 1 hour after a single observed ingestion. Cathartics and charcoal may be given but are probably not effective in single ingestions.
  - ▶ Fructose administration is contra-indicated due to side effects.
- Hydrogen peroxide at moderate concentrations (5% or more) is a strong oxidant.
- ▶ Direct contact with the eye is likely to cause corneal damage especially if not washed immediately. Careful ophthalmologic evaluation is recommended and the possibility of local corticosteroid therapy should be considered.
  - ▶ Because of the likelihood of systemic effects attempts at evacuating the stomach via emesis induction or gastric lavage should be avoided.
  - ▶ There is remote possibility, however, that a nasogastric or orogastric tube may be required for the reduction of severe distension due to gas formation"
- Fisher Scientific SDS

## SECTION 5 FIRE-FIGHTING MEASURES

### Extinguishing media

For hydrogen peroxide

NOTE: Chemical extinguishing agents may accelerate decomposition. [CCINFO]

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

### Special protective equipment and precautions for fire-fighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ Fight fire from a safe distance, with adequate cover.</li> <li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li> <li>▶ Use water delivered as a fine spray to control the fire and cool adjacent area.</li> <li>▶ Avoid spraying water onto liquid pools.</li> <li>▶ <b>Do not approach containers suspected to be hot.</b></li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat, flame and/or oxidisers.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include: carbon dioxide (CO<sub>2</sub>) other pyrolysis products typical of burning organic material.</p>

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> <li>▶ Contain and absorb small quantities with vermiculite or other absorbent material.</li> <li>▶ Wipe up.</li> <li>▶ Collect residues in a flammable waste container.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Water spray or fog may be used to disperse /absorb vapour.</li> </ul>

## Ethyl Alcohol Hand Sanitizer

- ▶ Contain spill with sand, earth or vermiculite.
  - ▶ Use only spark-free shovels and explosion proof equipment.
  - ▶ Collect recoverable product into labelled containers for recycling.
  - ▶ Absorb remaining product with sand, earth or vermiculite.
  - ▶ Collect solid residues and seal in labelled drums for disposal.
  - ▶ Wash area and prevent runoff into drains.
  - ▶ If contamination of drains or waterways occurs, advise emergency services.
- For hydrogen peroxide:
- ▶ Dilute with large quantities of water (at least ten (10) times the volume of hydrogen peroxide).
  - ▶ Sodium bicarbonate may be used to accelerate breakdown.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

## Precautions for safe handling

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights, heat or ignition sources.</li> <li>▶ When handling, <b>DO NOT eat, drink or smoke.</b></li> <li>▶ Vapour may ignite on pumping or pouring due to static electricity.</li> <li>▶ <b>DO NOT use plastic buckets.</b></li> <li>▶ Earth and secure metal containers when dispensing or pouring product.</li> <li>▶ Use spark-free tools when handling.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers in approved flame-proof area.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store away from incompatible materials in a cool, dry well ventilated area.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

## Conditions for safe storage, including any incompatibilities

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Packing as supplied by manufacturer.</li> <li>▶ Plastic containers may only be used if approved for flammable liquid.</li> <li>▶ Check that containers are clearly labelled and free from leaks.</li> <li>▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)</li> <li>▶ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)</li> <li>▶ Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.</li> <li>▶ Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages</li> <li>▶ In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</li> </ul> <p>Hydrogen peroxide containing/ generating materials requiring rigid packaging.</p> <p>Store in:</p> <ul style="list-style-type: none"> <li>▶ containers with vented lids.</li> <li>▶ properly passivated aluminium containers.</li> <li>▶ properly passivated stainless steel.</li> <li>▶ polyethylene containers.</li> <li>▶ porcelain, vitreous stoneware</li> <li>▶ Teflon lined containers.</li> </ul>
<b>Storage incompatibility</b>	<p>Hydrogen peroxide</p> <ul style="list-style-type: none"> <li>▶ is a powerful oxidiser</li> <li>▶ contamination or heat may cause self accelerating exothermic decomposition with oxygen gas and steam release - this may generate dangerous pressures - steam explosion.</li> <li>▶ reacts dangerously with rust, dust, dirt, iron, copper, acids, metals and salts, organic material.</li> <li>▶ is unstable if heated. (e.g): one volume of 70% hydrogen peroxide solution decomposes to produce 300 volumes of oxygen gas.</li> <li>▶ in presence of a strong initiating source may be explosively reactive</li> <li>▶ concentrated or pure material can generate heat and decompose spontaneously; can ignite or explode when heated, shocked, contaminated; or if placed in a basic (&gt;7) environment, especially in the presence of metal ions</li> <li>▶ mixtures with combustible materials may result in spontaneous combustion or may be impact- or heat- sensitive - evaporation or drying on towels or mop may cause a fire.</li> <li>▶ reacts violently with reducing agents, alcohols, ammonia, carboxylic acids, acetic acid, cobalt oxides, copper(II) chloride, ethers, metal powder, permanganates, acetone, benzenesulfonic anhydride, 1,1-dimethylhydrazine, dimethylphenylphosphine, gadolinium hydroxide,</li> </ul>

## Ethyl Alcohol Hand Sanitizer

- hydrogen selenide, iron oxides, lithium tetrahydroaluminate, magnesium tetrahydroaluminate, manganese(II) oxide, mercury oxide, methyl hydrazine, nickel monoxide, nitrogenous bases, osmium tetroxide, alpha-phenylselenoketones, phosphorus, phosphorus(V) oxide, quinoline, tetrahydrothiophene, tin(II) chloride, thiodiglycol, thiophane, tin(II) chloride, unsaturated organic compounds, readily oxidisable and combustible materials; avoid contact with combustibles including lubricants and graphite
- ▶ reacts with cobalt, copper and its alloys, chromium, iridium, iron, lead, manganese, Monel, osmium, palladium, platinum, gold, silver, zinc, and other catalytic metals, metal oxides and salts - avoid metallic bowls and stirrers.
  - ▶ violent catalytic decomposition will occur in contact with certain metals such as iron, copper, chromium, brass, bronze, lead, silver, manganese or their salts.
  - ▶ forms unstable and possible explosive materials with acetic anhydride, acetic acid, aniline, carboxylic acids, 1,4-diazabicyclo[2.2.2]octane, diphenyl diselenide, ethyl acetate, glycols, ketene, ketones, triethyltin hydroperoxide, 1,3,5-trioxane, vinyl acetate.
  - ▶ is incompatible with mercurous chloride
  - ▶ decomposes in presence of alkalis and even ordinary dust or rust
  - ▶ decomposes slowly at ordinary temperatures and builds up pressure in a closed container; the rate of decomposition doubles for each 10 deg C rise in temperature and decomposition becomes self-sustaining at 141 deg. C
  - ▶ contact with rough surfaces can cause decomposition
  - ▶ attacks and may ignite some plastics, rubber and coatings
  - ▶ Avoid oxidising agents, acids, acid chlorides, acid anhydrides, chloroformates.
  - ▶ Avoid strong bases.

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

## Control parameters

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

## INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	tertiary butanol	2-Methyl-2-propanol, Trimethyl carbinol	100 ppm / 300 mg/m3	450 mg/m3 / 150 ppm	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	tertiary butanol	tert-Butyl alcohol	100 ppm / 300 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	tertiary butanol	tert-Butanol	100 ppm	Not Available	Not Available	CNS impair
US NIOSH Recommended Exposure Limits (RELs)	ethanol	Alcohol, Cologne spirit, Ethanol, EtOH, Grain alcohol	1000 ppm / 1900 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ethanol	Ethyl alcohol (Ethanol)	1000 ppm / 1900 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ethanol	Ethanol	Not Available	1000 ppm	Not Available	URT irr
US NIOSH Recommended Exposure Limits (RELs)	hydrogen peroxide	High-strength hydrogen peroxide, Hydrogen dioxide, Hydrogen peroxide (aqueous), Hydroperoxide, Peroxide	1 ppm / 1.4 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	hydrogen peroxide	Hydrogen peroxide	1 ppm / 1.4 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	hydrogen peroxide	Hydrogen peroxide	1 ppm	Not Available	Not Available	Eye, URT, & skin irr
US NIOSH Recommended Exposure Limits (RELs)	glycerol	Glycerin (anhydrous); Glycerol; Glycyl alcohol; 1,2,3-Propanetriol; Trihydroxypropane	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Levels (PELs) - Table Z1	glycerol	Glycerin (mist): Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	glycerol	Glycerin (mist): Total dust	15 mg/m3	Not Available	Not Available	Not Available

## EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
tertiary butanol	Butyl alcohol, tert; (tert-Butanol)	150 ppm	1,300 ppm	8000* ppm
ethanol	Ethanol: (Ethyl alcohol)	Not Available	Not Available	15000* ppm
hydrogen peroxide	Hydrogen peroxide	Not Available	Not Available	Not Available
glycerol	Glycerine (mist); (Glycerol; Glycerin)	45 mg/m3	180 mg/m3	1,100 mg/m3

Ingredient	Original IDLH	Revised IDLH
water	Not Available	Not Available
tertiary butanol	1,600 ppm	Not Available
denatonium benzoate	Not Available	Not Available
ethanol	3,300 ppm	Not Available
hydrogen peroxide	75 ppm	Not Available
glycerol	Not Available	Not Available

## OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
denatonium benzoate	E	≤ 0.01 mg/m <sup>3</sup>

## Ethyl Alcohol Hand Sanitizer

## Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

## Exposure controls

<p><b>Appropriate engineering controls</b></p>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.</p> <p>Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1" data-bbox="389 629 1484 898"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s (50-100 f/min.)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1" data-bbox="389 954 1093 1122"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p>	Type of Contaminant:	Air Speed:	solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)	aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)	direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use	4: Large hood or large air mass in motion	4: Small hood-local control only
Type of Contaminant:	Air Speed:																		
solvent, vapours, degreasing etc., evaporating from tank (in still air).	0.25-0.5 m/s (50-100 f/min.)																		
aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)	0.5-1 m/s (100-200 f/min.)																		
direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)																		
Lower end of the range	Upper end of the range																		
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents																		
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity																		
3: Intermittent, low production.	3: High production, heavy use																		
4: Large hood or large air mass in motion	4: Small hood-local control only																		
<p><b>Personal protection</b></p>																			
<p><b>Eye and face protection</b></p>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>																		
<p><b>Skin protection</b></p>	<p>See Hand protection below</p>																		
<p><b>Hands/feet protection</b></p>	<ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>- frequency and duration of contact,</li> <li>- chemical resistance of glove material,</li> <li>- glove thickness and</li> <li>- dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>- When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> </ul>																		

## Ethyl Alcohol Hand Sanitizer

- Contaminated gloves should be replaced.
- As defined in ASTM F-739-96 in any application, gloves are rated as:
- Excellent when breakthrough time > 480 min
  - Good when breakthrough time > 20 min
  - Fair when breakthrough time < 20 min
  - Poor when glove material degrades
- For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.
- It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.
- Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
- Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
- Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
  - Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential
- Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.
- ▶ Where hydrogen peroxide exposure may occur do NOT wear PVA gloves.
  - ▶ DO NOT use leather or cotton gloves, leather shoes as spill may cause fire.
  - ▶ Care: Effects may be delayed.
  - ▶ Hand cream offers no protection for hydrogen peroxide and should not be used.

**Body protection** See Other protection below

**Other protection**

- ▶ Overalls.
- ▶ PVC Apron.
- ▶ PVC protective suit may be required if exposure severe.
- ▶ Eyewash unit.
- ▶ Ensure there is ready access to a safety shower.
- ▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- ▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).
- ▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot and shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.

**Recommended material(s)****GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Ethyl Alcohol Hand Sanitizer

Material	CPI
BUTYL	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
NITRILE+PVC	C
PE/EVAL/PE	C
PVA	C
PVC	C
VITON	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

**Respiratory protection**

**Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)**

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS	-	A-PAPR-AUS / Class 1
up to 50 x ES	-	A-AUS / Class 1	-
up to 100 x ES	-	A-2	A-PAPR-2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

**SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Appearance</b>	Colorless
-------------------	-----------



## Ethyl Alcohol Hand Sanitizer

Physical state	Liquid	Relative density (Water = 1)	0.863
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	20.56	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

## SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul> Solutions of hydrogen peroxide slowly decompose, releasing oxygen, and so are often stabilised by the addition of acetanilide, etc.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

Inhaled	<p>The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.</p> <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p> <p>Animal testing shows that the most common signs of inhalation overdose is inco-ordination and drowsiness.</p> <p>Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.</p> <p>Inhaling excessive levels of mist may result in headache, dizziness, vomiting, diarrhoea, irritability, sleeplessness and fluid in the lungs, and cause extreme irritation of the nose and chest, cough, discomfort, shortness of breath and inflammation of the nose and throat. Whole-body effects of hydrogen peroxide poisoning include tremor, numbness of the limbs, convulsions, coma and shock. Hydrogen peroxide has poor warning properties.</p> <p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p>						
Ingestion	<p>Ingestion of ethanol (ethyl alcohol, "alcohol") may produce nausea, vomiting, bleeding from the digestive tract, abdominal pain, and diarrhoea. Effects on the body:</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 30%;">Blood concentration</th> <th>Effects</th> </tr> </thead> <tbody> <tr> <td>&lt;1.5 g/L</td> <td>Mild: impaired vision, co-ordination and reaction time; emotional instability</td> </tr> <tr> <td>1.5-3.0 g/L</td> <td>Moderate: Slurred speech, confusion, inco-ordination, emotional instability, disturbances in perception and senses, possible blackouts, and impaired objective performance in standardized tests. Possible double vision, flushing, fast heart rate, sweating and incontinence. Slow breathing may occur rarely and fast breathing may develop in cases of metabolic acidosis, low blood sugar and low blood potassium. Central nervous system depression may progress to coma.</td> </tr> </tbody> </table>	Blood concentration	Effects	<1.5 g/L	Mild: impaired vision, co-ordination and reaction time; emotional instability	1.5-3.0 g/L	Moderate: Slurred speech, confusion, inco-ordination, emotional instability, disturbances in perception and senses, possible blackouts, and impaired objective performance in standardized tests. Possible double vision, flushing, fast heart rate, sweating and incontinence. Slow breathing may occur rarely and fast breathing may develop in cases of metabolic acidosis, low blood sugar and low blood potassium. Central nervous system depression may progress to coma.
Blood concentration	Effects						
<1.5 g/L	Mild: impaired vision, co-ordination and reaction time; emotional instability						
1.5-3.0 g/L	Moderate: Slurred speech, confusion, inco-ordination, emotional instability, disturbances in perception and senses, possible blackouts, and impaired objective performance in standardized tests. Possible double vision, flushing, fast heart rate, sweating and incontinence. Slow breathing may occur rarely and fast breathing may develop in cases of metabolic acidosis, low blood sugar and low blood potassium. Central nervous system depression may progress to coma.						



## Ethyl Alcohol Hand Sanitizer

	<p>3-5 g/L</p> <p>Severe: cold clammy skin, low body temperature and low blood pressure. Atrial fibrillation and heart block have been reported. Depression of breathing may occur, respiratory failure may follow serious poisoning, choking on vomit may result in lung inflammation and swelling. Convulsions due to severe low blood sugar may also occur. Acute liver inflammation may develop.</p>	<p>The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.</p> <p>Hydrogen peroxide may cause blistering and bleeding from the throat and stomach. When swallowed, it may release large quantities of oxygen which could hyper-distend the stomach and gut and may cause internal bleeding, mouth and throat burns and rupture of the gut. There may also be fever, nausea, foaming at the mouth, vomiting, chest and stomach pain, loss of consciousness, and movement disorders and death. Large amounts can also cause cessation of breath, dizziness, headache, tremors weakness or numbness in the extremities and convulsions. Hydrogen peroxide concentrate is corrosive and must not be taken undiluted.</p> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p>														
Skin Contact	<p>Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>Hydrogen peroxide is used topically as dental gel and to clean minor wounds. It may cause dose dependent effect on the skin including bleaching, blistering, reddening and corrosion ( at &gt;50% concentration).</p> <p>There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p>															
Eye	<p>Direct contact of the eye with ethanol (alcohol) may cause an immediate stinging and burning sensation, with reflex closure of the lid, and a temporary, tearing injury to the cornea together with redness of the conjunctiva. Discomfort may last 2 days but usually the injury heals without treatment.</p> <p>Hydrogen peroxide concentrations above 10% are corrosive to the eye and may cause corneal ulceration even days after exposure.</p> <p>There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.</p>															
Chronic	<p>Based on experiments and other information, there is ample evidence to presume that exposure to this material can cause genetic defects that can be inherited.</p> <p>Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Ample evidence exists that this material directly causes reduced fertility</p> <p>Prolonged exposure to ethanol may cause damage to the liver and cause scarring. It may also worsen damage caused by other agents.</p> <p>Hydrogen peroxide as a human food additive is generally regarded as safe, when used with certain limitations. In experimental animals hydrogen peroxide given by mouth causes damage to the teeth, liver, kidney, stomach and bowel. Inhalation exposure to hydrogen peroxide caused skin irritation, sneezing and death in animals. Skin irritation, sneezing, excessive secretion of tears, and whitening of the hair was also seen in animals chronically exposed to hydrogen peroxide.</p>															
Ethyl Alcohol Hand Sanitizer	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Not Available</td> <td>Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Not Available	Not Available											
TOXICITY	IRRITATION															
Not Available	Not Available															
water	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Oral (rat) LD50: &gt;90000 mg/kg<sup>[2]</sup></td> <td>Not Available</td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Oral (rat) LD50: >90000 mg/kg <sup>[2]</sup>	Not Available											
TOXICITY	IRRITATION															
Oral (rat) LD50: >90000 mg/kg <sup>[2]</sup>	Not Available															
tertiary butanol	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Dermal (rabbit) LD50: &gt;2000 mg/kg<sup>[2]</sup></td> <td>Eye: adverse effect observed (irritating)<sup>[1]</sup></td> </tr> <tr> <td>Inhalation (rat) LC50: &gt;9988.59 mg/l/4H<sup>[2]</sup></td> <td>Skin: adverse effect observed (irritating)<sup>[1]</sup></td> </tr> <tr> <td>Oral (rat) LD50: 1500 mg/kg<sup>[2]</sup></td> <td>Skin: no adverse effect observed (not irritating)<sup>[1]</sup></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>	Inhalation (rat) LC50: >9988.59 mg/l/4H <sup>[2]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>	Oral (rat) LD50: 1500 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>							
TOXICITY	IRRITATION															
Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>															
Inhalation (rat) LC50: >9988.59 mg/l/4H <sup>[2]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>															
Oral (rat) LD50: 1500 mg/kg <sup>[2]</sup>	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>															
denatonium benzoate	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>dermal (rat) LD50: &gt;2000 mg/kg<sup>[1]</sup></td> <td>Eye: adverse effect observed (irreversible damage)<sup>[1]</sup></td> </tr> <tr> <td>Inhalation (rat) LC50: 0.2 mg/l/4H<sup>[2]</sup></td> <td>Skin: adverse effect observed (irritating)<sup>[1]</sup></td> </tr> <tr> <td>Oral (rat) LD50: 584 mg/kg<sup>[2]</sup></td> <td></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irreversible damage) <sup>[1]</sup>	Inhalation (rat) LC50: 0.2 mg/l/4H <sup>[2]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>	Oral (rat) LD50: 584 mg/kg <sup>[2]</sup>								
TOXICITY	IRRITATION															
dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irreversible damage) <sup>[1]</sup>															
Inhalation (rat) LC50: 0.2 mg/l/4H <sup>[2]</sup>	Skin: adverse effect observed (irritating) <sup>[1]</sup>															
Oral (rat) LD50: 584 mg/kg <sup>[2]</sup>																
ethanol	<table border="1"> <thead> <tr> <th>TOXICITY</th> <th>IRRITATION</th> </tr> </thead> <tbody> <tr> <td>Inhalation (rat) LC50: 124.7 mg/l/4H<sup>[2]</sup></td> <td>Eye (rabbit): 500 mg SEVERE</td> </tr> <tr> <td>Oral (rat) LD50: =1501 mg/kg<sup>[2]</sup></td> <td>Eye (rabbit):100mg/24hr-moderate</td> </tr> <tr> <td></td> <td>Eye: adverse effect observed (irritating)<sup>[1]</sup></td> </tr> <tr> <td></td> <td>Skin (rabbit):20 mg/24hr-moderate</td> </tr> <tr> <td></td> <td>Skin (rabbit):400 mg (open)-mild</td> </tr> <tr> <td></td> <td>Skin: no adverse effect observed (not irritating)<sup>[1]</sup></td> </tr> </tbody> </table>	TOXICITY	IRRITATION	Inhalation (rat) LC50: 124.7 mg/l/4H <sup>[2]</sup>	Eye (rabbit): 500 mg SEVERE	Oral (rat) LD50: =1501 mg/kg <sup>[2]</sup>	Eye (rabbit):100mg/24hr-moderate		Eye: adverse effect observed (irritating) <sup>[1]</sup>		Skin (rabbit):20 mg/24hr-moderate		Skin (rabbit):400 mg (open)-mild		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
TOXICITY	IRRITATION															
Inhalation (rat) LC50: 124.7 mg/l/4H <sup>[2]</sup>	Eye (rabbit): 500 mg SEVERE															
Oral (rat) LD50: =1501 mg/kg <sup>[2]</sup>	Eye (rabbit):100mg/24hr-moderate															
	Eye: adverse effect observed (irritating) <sup>[1]</sup>															
	Skin (rabbit):20 mg/24hr-moderate															
	Skin (rabbit):400 mg (open)-mild															
	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>															

## Ethyl Alcohol Hand Sanitizer

hydrogen peroxide	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[2]</sup>	Not Available
	Inhalation (rat) LC50: 2 mg/l/4H <sup>[2]</sup>	
	Oral (rat) LD50: >225 mg/kg <sup>[2]</sup>	
glycerol	<b>TOXICITY</b>	<b>IRRITATION</b>
	Oral (rat) LD50: >10000 mg/kg <sup>[2]</sup>	Not Available
<b>Legend:</b>	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

<b>DENATONIUM BENZOATE</b>	<p>Somnolence, tremor, ataxia recorded.</p> <p>Most undiluted cationic surfactants satisfy the criteria for classification as Harmful (Xn) with R22 and as Irritant (Xi) for skin and eyes with R38 and R41.</p> <p>For quaternary ammonium compounds (QACs):</p> <p>Quaternary ammonium compounds are synthetically made surfactants. Studies show that its solubility, toxicity and irritation depend on chain length and bond type while effect on histamine depends on concentration. QACs may cause muscle paralysis with no brain involvement. There is a significant association between the development of asthma symptoms and the use of QACs as disinfectant.</p>
<b>ETHANOL</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
<b>HYDROGEN PEROXIDE</b>	<p>Exposure to hydrogen peroxide via the skin or oral route can produce toxic effects. Animal studies have shown evidence of damage to the kidney, gut, thymus and liver. Stomach and intestinal lesions including benign and malignant cancers have been observed in mice. It may produce genetic and developmental defects but no reproductive toxicity was reported in mice.</p> <p>The substance is classified by IARC as Group 3:  <b>NOT</b> classifiable as to its carcinogenicity to humans.  Evidence of carcinogenicity may be inadequate or limited in animal testing.</p>
<b>GLYCEROL</b>	At very high concentrations, evidence predicts that glycerol may cause tremor, irritation of the skin, eyes, digestive tract and airway. Otherwise it is of low toxicity. There is no significant evidence to suggest that it causes cancer, genetic, reproductive or developmental toxicity.
<b>WATER &amp; HYDROGEN PEROXIDE</b>	No significant acute toxicological data identified in literature search.
<b>TERTIARY BUTANOL &amp; DENATONIUM BENZOATE &amp; HYDROGEN PEROXIDE &amp; GLYCEROL</b>	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

<b>Acute Toxicity</b>	✗	<b>Carcinogenicity</b>	✗
<b>Skin Irritation/Corrosion</b>	✗	<b>Reproductivity</b>	✗
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT - Single Exposure</b>	✗
<b>Respiratory or Skin sensitisation</b>	✗	<b>STOT - Repeated Exposure</b>	✗
<b>Mutagenicity</b>	✗	<b>Aspiration Hazard</b>	✗

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

Ethyl Alcohol Hand Sanitizer	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available		Not Available	Not Available
water	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	897.520mg/L	3
	EC50	96	Algae or other aquatic plants	8768.874mg/L	3
tertiary butanol	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	106.428mg/L	3
	EC50	48	Crustacea	5-504mg/L	2
	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	NOEC	72	Algae or other aquatic plants	1-mg/L	2
denatonium benzoate	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>1-mg/L	2
	EC50	48	Crustacea	>500mg/L	2

Continued...

## Ethyl Alcohol Hand Sanitizer

	EC50	72	Algae or other aquatic plants	>100mg/L	2
	NOEC	48	Crustacea	50mg/L	2
ethanol	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	11-mg/L	2
	EC50	48	Crustacea	2mg/L	4
	EC50	96	Algae or other aquatic plants	17.921mg/L	4
	NOEC	2016	Fish	0.000375mg/L	4
hydrogen peroxide	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.020mg/L	3
	EC50	48	Crustacea	2mg/L	2
	EC50	72	Algae or other aquatic plants	0.71mg/L	4
	EC0	24	Crustacea	1.1mg/L	2
	NOEC	192	Fish	0.028mg/L	4
glycerol	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>0.011-mg/L	2
	EC50	96	Algae or other aquatic plants	77712.039mg/L	3
<b>Legend:</b>	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

## For Ethanol:

log Kow: -0.31 to -0.32;  
 Koc 1: Estimated BCF= 3;  
 Half-life (hr) air: 144;  
 Half-life (hr) H2O surface water: 144;  
 Henry's atm m<sup>3</sup>/mol: 6.29E-06;  
 BOD 5 if unstated: 0.93-1.67,63%  
 COD: 1.99-2.11,97%;  
 ThOD : 2.1.

Environmental Fate: Terrestrial - Ethanol quickly biodegrades in soil but may leach into ground water; most is lost by evaporation. Ethanol is expected to have very high mobility in soil. Volatilization of ethanol from moist soil surfaces is expected to be an important fate process. The potential for volatilization of ethanol from dry soil surfaces may exist. Biodegradation is expected to be an important fate process for ethanol based on half-lives on the order of a few days for ethanol in sandy soil/groundwater microcosms.

Atmospheric Fate: Ethanol is expected to exist solely as a vapour in the ambient atmosphere. Vapour-phase ethanol is degraded in the atmosphere by reaction with photochemically-produced hydroxyl radicals; the half-life for this reaction in air is estimated to be 5 days. Ethanol readily degraded by reaction with photochemically produced hydroxy radicals; release into air will result in photodegradation and wet deposition.

Aquatic Fate: When released into water ethanol readily evaporates and is biodegradable. Ethanol is not expected to adsorb to suspended solids and sediment. Volatilization from water surfaces is expected and volatilization half-lives for a model river and model lake are 3 and 39 days, respectively. Bioconcentration in aquatic organisms is considered to be low. Hydrolysis and photolysis in sunlit surface waters is not expected to be an important environmental fate process for ethanol and is unlikely to be persistent in aquatic environments.

## For hydrogen peroxide:log Kow: -1.36:

Environmental Fate: Hydrogen peroxide is a naturally occurring substance (typical background concentrations < 1 - 30 g/l), which is produced by almost all cells in their metabolism, with the exception of anaerobic bacteria. Hydrogen peroxide is a reactive substance in the presence of other substances, elements, radiation, materials and can be degraded by micro-organisms or higher organisms. Air - Hydrogen peroxide is degraded by light and thus may be removed from the atmosphere by photolysis giving rise to hydroxyl radicals, by reaction with hydroxyl radicals, or by heterogenous loss processes such as rain-out. Significantly higher hydrogen peroxide concentrations are found in polluted atmospheres as compared with clean air, presumably due to oxidation of reactive hydrocarbons as a result of exposure to light. Soil - No information was found regarding the transformation or persistence of hydrogen peroxide in soil, however, solutions of hydrogen peroxide gradually deteriorate. Water - Hydrogen peroxide is a naturally occurring substance. Surface water concentrations of hydrogen peroxide have been found to vary between 51-231 mg/L, increasing both with exposure to sunlight and the presence of dissolved organic matter. Hydrogen peroxide degrades by various mechanisms, including chemical reduction and enzymatic decomposition by algae, zooplankton, and bacteria. However microorganisms, especially bacteria, account for the majority of degradation. The rate of decomposition in natural water varies from a few minutes to more than a week, depending on numerous chemical, biological, and physical factors. Hydrogen peroxide is rapidly degraded in a biological waste water treatment plant. Hydrogen peroxide adsorbs poorly to sediment particles and is rapidly degraded, thus accumulation in the sediment is also not expected. Hydrogen peroxide (log Kow < -1) is an inorganic substance and therefore shows little potential to bioaccumulate.

Ecotoxicity: Fish LC50 (96 h): catfish 37.4 mg/l/Fish LC50 (24 h): mackerel 89 mg/l; chameleon gobi 155 mg/l/Zebra mussel LC50 (28 h) 30 mg/l; (228 h): 12 mg/l Ecotoxicity data show that microorganisms (i.e., bacteria, algae) and zooplankton present in aquatic ecosystems are generally less tolerant of hydrogen peroxide exposure than fish or other vertebrates. Effects of short-term exposures on sensitive bacteria and invertebrates (e.g., Daphnia pulex) have been observed at concentrations in the low mg/L (ppm) range, while effects on sensitive algae have been reported at levels less than 1.0 mg/L. Algae are the most sensitive species for hydrogen peroxide. The algal EC50 of hydrogen peroxide was 1.6-5 mg/l, while the NOEC was 0.1 mg/l. In a 21-d continuous exposure study on Daphnia magna, the chronic no observable effect concentration (NOEC) for reproduction was 0.63 mg/L and the NOEC for mortality was 1.25 mg/L. In chronic toxicity studies with invertebrates (zebra mussels) and hydrogen peroxide shows a NOEC of 2 mg/l. The PNEC of hydrogen peroxide is equal to 10 ug/l. Risk mitigation is needed to ensure that use of hydrogen peroxide will not adversely impact aquatic life. An acute water quality criterion or "benchmark" has been determined. For hydrogen peroxide, the acute benchmark is 0.7 mg/L. This value was calculated using the extensive toxicity database for hydrogen peroxide and procedures in U.S. Environmental Protection Agency guidance for deriving numerical national water quality criteria. The use of hydrogen peroxide in intensive aquaculture in finfish (at up to 100 mg/L for 60 minutes) and finfish eggs (at up to 1,000 mg/L for 15 minutes) is not expected to have a significant impact on the environment.

**DO NOT discharge into sewer or waterways.**

## Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW
tertiary butanol	HIGH (Half-life = 360 days)	LOW (Half-life = 24.58 days)
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
hydrogen peroxide	LOW	LOW
glycerol	LOW	LOW

## Ethyl Alcohol Hand Sanitizer

## Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)
tertiary butanol	LOW (BCF = 1.09)
ethanol	LOW (LogKOW = -0.31)
hydrogen peroxide	LOW (LogKOW = -1.571)
glycerol	LOW (LogKOW = -1.76)

## Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)
tertiary butanol	HIGH (KOC = 1.471)
ethanol	HIGH (KOC = 1)
hydrogen peroxide	LOW (KOC = 14.3)
glycerol	HIGH (KOC = 1)


## SECTION 13 DISPOSAL CONSIDERATIONS

## Waste treatment methods

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li> </ul>
-------------------------------------	--

## SECTION 14 TRANSPORT INFORMATION

## Labels Required

	
<b>Marine Pollutant</b>	NO

## Land transport (DOT)

<b>UN number</b>	1170				
<b>UN proper shipping name</b>	Ethanol or Ethyl alcohol or Ethanol solutions or Ethyl alcohol solutions				
<b>Transport hazard class(es)</b>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 150px;">Class</td> <td style="border-left: 1px dashed black;">3</td> </tr> <tr> <td>Subrisk</td> <td style="border-left: 1px dashed black;">Not Applicable</td> </tr> </table>	Class	3	Subrisk	Not Applicable
Class	3				
Subrisk	Not Applicable				
<b>Packing group</b>	II				
<b>Environmental hazard</b>	Not Applicable				
<b>Special precautions for user</b>	<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 150px;">Hazard Label</td> <td style="border-left: 1px dashed black;">3</td> </tr> <tr> <td>Special provisions</td> <td style="border-left: 1px dashed black;">24, IB2, T4, TP1</td> </tr> </table>	Hazard Label	3	Special provisions	24, IB2, T4, TP1
Hazard Label	3				
Special provisions	24, IB2, T4, TP1				

## Ethyl Alcohol Hand Sanitizer

## Air transport (ICAO-IATA / DGR)

<b>UN number</b>	1170	
<b>UN proper shipping name</b>	Ethanol or Ethanol. solution	
<b>Transport hazard class(es)</b>	ICAO/IATA Class	3
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	3L
<b>Packing group</b>	II	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	Special provisions	A3 A58 A180
	Cargo Only Packing Instructions	364
	Cargo Only Maximum Qty / Pack	60 L
	Passenger and Cargo Packing Instructions	353
	Passenger and Cargo Maximum Qty / Pack	5 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y341
	Passenger and Cargo Limited Maximum Qty / Pack	1 L

## Sea transport (IMDG-Code / GGVSee)

<b>UN number</b>	1170	
<b>UN proper shipping name</b>	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	
<b>Transport hazard class(es)</b>	IMDG Class	3
	IMDG Subrisk	Not Applicable
<b>Packing group</b>	II	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	EMS Number	F-E , S-D
	Special provisions	144
	Limited Quantities	1 L

## Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## SECTION 15 REGULATORY INFORMATION

## Safety, health and environmental regulations / legislation specific for the substance or mixture

## WATER IS FOUND ON THE FOLLOWING REGULATORY LISTS

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

## TERTIARY BUTANOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

US ACGIH Threshold Limit Values (Spanish)  
 US ACGIH Threshold Limit Values (TLV)  
 US AIHA Workplace Environmental Exposure Levels (WEELs)  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US EPCRA Section 313 Chemical List  
 US NIOSH Recommended Exposure Limits (RELs)  
 US NIOSH Recommended Exposure Limits (RELs) (Spanish)  
 US OSHA Permissible Exposure Levels (PELs) - Table Z1  
 US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

## DENATONIUM BENZOATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

US List of Active Substances Exempt from the TSCA Inventory Notifications (Active-Inactive) Rule  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

## ETHANOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

US ACGIH Threshold Limit Values (Spanish)  
 US ACGIH Threshold Limit Values (TLV)  
 US AIHA Workplace Environmental Exposure Levels (WEELs)  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US NIOSH Recommended Exposure Limits (RELs)  
 US NIOSH Recommended Exposure Limits (RELs) (Spanish)  
 US OSHA Permissible Exposure Levels (PELs) - Table Z1  
 US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)

Continued...

## Ethyl Alcohol Hand Sanitizer

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

**HYDROGEN PEROXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS**

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs  
 US ACGIH Threshold Limit Values (Spanish)  
 US ACGIH Threshold Limit Values (TLV)  
 US AIHA Workplace Environmental Exposure Levels (WEELs)  
 US Department of Homeland Security (DHS) - Chemical Facility Anti-Terrorism Standards (CFATS) - Chemicals of Interest  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US NIOSH Recommended Exposure Limits (RELs)  
 US NIOSH Recommended Exposure Limits (RELs) (Spanish)  
 US OSHA Permissible Exposure Levels (PELs) - Table Z1  
 US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)  
 US SARA Section 302 Extremely Hazardous Substances  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

**GLYCEROL IS FOUND ON THE FOLLOWING REGULATORY LISTS**

US ACGIH Threshold Limit Values (Spanish)  
 US DOE Temporary Emergency Exposure Limits (TEELs)  
 US NIOSH Recommended Exposure Limits (RELs)  
 US NIOSH Recommended Exposure Limits (RELs) (Spanish)  
 US OSHA Permissible Exposure Levels (PELs) - Table Z1  
 US OSHA Permissible Exposure Limits - Annotated Table Z-1 (Spanish)  
 US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory  
 US TSCA Chemical Substance Inventory - Interim List of Active Substances

**Federal Regulations****Superfund Amendments and Reauthorization Act of 1986 (SARA)****SECTION 311/312 HAZARD CATEGORIES**

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	No
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

**US. EPA CERCLA HAZARDOUS SUBSTANCES AND REPORTABLE QUANTITIES (40 CFR 302.4)**

None Reported

**State Regulations****US. CALIFORNIA PROPOSITION 65**

None Reported

**National Inventory Status**

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes

Continued...

## Ethyl Alcohol Hand Sanitizer

Canada - NDSL	No (hydrogen peroxide; glycerol; tertiary butanol; ethanol; water; denatonium benzoate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (denatonium benzoate)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

## SECTION 16 OTHER INFORMATION

<b>Revision Date</b>	04/03/2020
<b>Initial Date</b>	03/24/2020

## SDS Version Summary

Version	Issue Date	Sections Updated
1.6.1.1.1	04/02/2020	Ingredients

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## Definitions and abbreviations

PC—TWA: Permissible Concentration-Time Weighted Average  
 PC—STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit.  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.